



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



3-STAGE AIR HYDRAULIC JACK

SKU: N/A

3-Stage air hydraulic jack for low buses trucks and other low clearance vehicles

Categories: [Uncategorized](#)

PRODUCT DESCRIPTION

Minimum height of only 150 mm combined with a high lifting capacity
Telescopic cylinders ensure a high capacity combined with a low minimum height
Designed for heavy-duty, intensive commercial use

SAFETY

Built-in overload valve and dead man's release for optimum safety whilst lifting and lowering

ERGONOMICS

Ergonomic handle with push buttons

EXTENSIONS INCLUDED

Extend the maximum lifting height with an additional 50 or 100 mm

Capacity:50 t

Min height:150 mm

Max height:335 mm

Frame length:810 mm

Handle length:1160 mm

Width:200 mm

Width with wheels:310 mm

Air supply:9 - 10 bar

Air consumption:350 - l/min

Weight:67 kg

Item number:4500000

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.