Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

3-STAGE AIR HYDRAULIC JACK

SKU: N/A

3-Stage air hydraulic jack for high clearance vehicles

Categories: Uncategorized

PRODUCT DESCRIPTION

Minimum height of 220 mm and tall maximum height of 560 mm
Designed for heavy-duty, intensive commercial use
Telescopic cylinders ensure a high capacity combined with a low minimum height
Hard chromium plated rams for long life
For safety reasons, extensions are not included

SAFETY
Built-in overload valve and dead man's release for optimum safety whilst lifting and lowering
ERGONOMICS
Ergonomic handle with push buttons
WIDE LIFTING RANGE
Minimum height of 220 mm and high maximum height of 560 mm

Capacity: 50 t
Min height: 220 mm
Max height: 560 mm
Frame length: 810 mm
Handle length: 1160 mm
Width: 200 mm
Width with wheels: 310 mm
Air supply: 9 - 10 bar
Air consumption: 350 - l/min
Weight: 73 kg
Item number: 4503000

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you

Copyright © 2023 Actik Tools All rights reserved

verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools

All rights reserved