



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## ANSELL CHEMICAL PROTECTIVE GLOVE ALPHATEC 58-430 SIZE 10 BOTTLE GREEN/ANTHRACITE GREY EN 388, EN 374, EN 1149 PPE CATEGORY III

**SKU:** 0076490470906



12,00 PA Chemical protective glove AlphaTec 58-430 size 10 bottle green/anthracite grey EN 388, EN 374, EN 1149 PPE category III

---

**Categories:** [Chemical protection gloves](#), [Hand protections](#)

**Product Features:** Size: 10  
Length approx.: 320 mm  
Colour: Bottle green/anthracite grey  
Cut resistance acc. to EN ISO (Newton): X  
Brand: ANSELL  
EN 374-1 type: A  
Material: Cotton velour with nitrile, grip technolog  
[Datasheet](#)

Scope of delivery:  
12,00 PA Chemical protective glove AlphaTec 58-430 size 10 bottle green/anthracite grey EN 388, EN 374, EN 1149 PPE category III |

## PRODUCT DESCRIPTION

Complies with EN 388

- EN 374
- Cat. III
- Material: Cotton velour with nitrile coating
- Ansell Grip Technology®
- Optimally controlled wet and oil grip
- Little effort required for gripping
- Flexibility and finger dexterity
- Close, thus secure fit
- Protection against bases, oils, fuels and some solvents, greases and animal fats



- Suitable for medium loads
- Excellent protection against lacerations, punctures and abrasions
- Silicone-free
- Antistatic in accordance with EN 1149
- QLV: 0.65
- Application: Chemical processing, petrochemicals, handling of paints, inks, dyes, glues and adhesives, rubber and rubber additives, handling of fluid-impacted metal parts, maintenance of industrial tools, disposal of used oil, waste and water treatment Further technical information:
- Material suitable for craft and trade: Somewhat suitable
- Abrasion resistance: 3
- Tear propagation resistance: 0
- Puncture resistance: 1
- Cut resistance (cutting test): 0
- Material suitable for industry: Very suitable
- Food-grade material: Very suitable
- Type: Antistatic, protective cuff
- Standard: EN 388, EN 374, EN 1149
- Material suitable for assembly + workshop: Very suitable
- Chemical resistance: J = n-heptane / K = sodium hydroxide 40 % / L = sulphuric acid 96 % / O = ammonia 25 % / P = hydrogen peroxide 30 % / T = formaldehyde 37 % Also available in sizes 7, 8 and 11 on request

#### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.