



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ATG CUT-RESISTANT GLOVE
MAXICUT®OIL 44-305 SIZE 10
GREEN/BLACK EN 388 PPE CATEGORY
II UHMWPE/GLASS
FIB./NYL./POLYESTER/SPANDEX

SKU: 4792249070475

Cut-resistant glove MaxiCut®Oil 44-305 size 10 green/black EN 388 PPE category II UHMWPE/glass fib./nyl./polyester/spandex

Categories: <u>Cut-resistant and puncture-proof</u> <u>gloves and arm protectors</u>, <u>Hand protections</u>

Product Features: Size: 10 Length approx.: 245 mm Colour: Green/black

Brand: ATG PPE category: II

Cut resistance (cutting test): 3 Type: Knitted cuff, 3/4 coating

Material:

UHMWPE/fibreglass/nylon/polyester/elas

Datasheet

Scope of delivery:
12,00 PA Cut-resistant glove MaxiCut®Oil□
44-305 size 10 green/black EN 388 PPE
category II UHMWPE/glass
fib./nyl./polyester/spandex |

PRODUCT DESCRIPTION

Complies with EN 388:2016, EN 407:2020

- Cat. II
- Material: UHMWPE/fibreglass/nylon
- Polyester, spandex
- Slip-resistant nitrile coating with "Micro-Cup" surface
- 3/4 coated
- Cut resistance class B
- Liquid-repellent





- Superb fit
- Excellent flexibility
- Extremely high abrasion resistance, high wearing comfort thanks to seamless knitted lining
- Firmly closing cuff for a secure fit
- Silicone-free
- Pre-washed
- Washable at up to 40 °C
- Öko-Tex®-certified
- Skin Health Alliance seal of approval
- Application: Automotive industry, assembling/building machines, workshops, maintenance and repair, CNC production, construction and trade, disposal and recycling, mineral oil industry, handling cooling liquids, oils and greases, forestry, agriculture, gardening, household, hobby Further technical information:
- Material suitable for craft and trade: Very suitable
- Abrasion resistance: 4
- Material suitable for building + garden: Somewhat suitable
- Material suitable for industry: Very suitable
- Material suitable for logistics: Very suitable
- Tear propagation resistance: 4
- Puncture resistance: 1
- Cut resistance acc. to EN ISO (Newton): B
- Thickness approx.: 1.1mm
- Material suitable for assembly + workshop: Very suitable Also available from size 7 and in size 11 on request

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.