Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



# BENNING CLAMP-ON AMMETER MULTIMETER CM 10-1 0.01-1500 A CAT IV 600 V, CAT III 100 V

**SKU:** 4014651446885

Clamp-on ammeter multimeter CM 10-1 0.01-1500 A CAT IV 600 V, CAT III 100 V

---

**Categories:** Clamp-on ammeters, Measuring and testers for electrical installation

**Product Features:** Measuring technique: TRUE RMS
Measurement category: CAT IV 600 V, CAT III 100 V
Measuring range: 0.01-1500 A
Brand: BENNING
Datasheet

Scope of delivery:
1,00 ST Clamp-on ammeter multimeter CM 10-1 0.01-1500 A CAT IV 600 V, CAT III 100 V |

## PRODUCT DESCRIPTION

Illuminated 4-digit digital LCD display (6,000 pixels)
- For professional use in industry, service and trade
- Continuity testing
- Diode testing
- Data logger and memory function (4,000 measured values)
- Bluetooth® Low Energy 4.0 interface for transferring measured values
- Free IOS and Android app BENNING MM-CM Link for downloading, storing and sharing measured values via smartphone/tablet. AutoV function with low impedance (LoZ) for suppressing reactive voltages
- Inrush current measurement (INRUSH)
- Low pass filter (HFR high-frequency suppression, 800 Hz) for measurements on cycled motor drives
- Measurement input for flexible current transformer BENNING CFlex 1 bis 3,000 A AC (optional accessory)
- Volt sensor for contactless phase and cable break testing (red LED)
- Automatic measuring range selection, shut-off, battery undervoltage display
- Current value memory - Hold
- Minimum/maximum value memory (MIN/MAX)

Copyright © 2023 Actik Tools All rights reserved

- LED measuring point illumination
- Measuring circuit category Cat IV 600 V, Cat III 1,000 V Measuring ranges: Alternating voltage (0.1 V-1,000 V direct voltage (0.1 mV-1,000 V alternating/direct current 0.01 A-1,500 A, resistance 0.1 -600 k, frequency 0.01 Hz-10 kHz, capacitance 0.1 F-1 mF Further technical information:
- Width: 86mm
- Length: 254mm
- Opening of pliers: 42mm
- Height: 48mm Supplied with bag, measuring lines, batteries (2 x type AA) For replacement battery, see article 4000 901 811 Note on the disposal of batteries and rechargeable batteries As we sell batteries and rechargeable batteries and devices that contain batteries and rechargeable batteries, under the German Battery Act (BattG we are obliged to draw your attention to the following: The symbol of the waste bin with the X through it on batteries and rechargeable batteries means that they must not be disposed on in household waste after consumption. If batteries or rechargeable batteries contain mercury, cadmium or lead, you will find the chemical symbol (Hg, Cd or Pb) under the symbol of the waste bin with the X through it. Every user of batteries or rechargeable batteries is legally obliged to return old batteries and rechargeable batteries. They can be returned, free of charge, to the retailer or another collection point near you. You can obtain the addresses of suitable collection points near you from your local government authority. In the case of batteries that contain more than 0.0005 percent by mass mercury, more than 0.002 percent by mass cadmium or more than 0.004 percent by mass lead, the chemical symbols of the respective harmful substance used are indicated under the waste bin symbol. The chemical symbols have the following meaning: Pb: Battery contains lead Cd: Battery contains cadmium Hg: Battery contains mercury

**PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved