



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



**BESSEY SURFACE CLAMP UK
CLAMPING WIDTH 600 MM RADIUS 80
MM MIN./MAX. SPREADING WIDTH
172 / 270 MM**

SKU: 4008158027210

1,00 ST Surface clamp UK clamping width 600 mm radius 80 mm min./max. spreading width 172 / 270 mm

Categories: [Clamping tools](#), [Surface clamps and body clamps](#)

Product Features: Clamping width: 600 mm
Radius: 80 mm
Min./max. spreading width: 172/270 mm
Brand: BESSEY
Clamping force: Up to 1,500 N

Scope of delivery:
1,00 ST Surface clamp UK clamping width 600 mm radius 80 mm min./max. spreading width 172 / 270 mm |

PRODUCT DESCRIPTION

For clamping and spreading

- Hollow-profile rail made of drawn, high-grade steel
- 2x corrugated
- Zinc galvanised
- Sliding and fixed bracket made of die-cast zinc, galvanically zinc-coated
- Smooth-running, burnished spindle with trapezoidal thread
- Plastic trays made of glass-fibre-reinforced, glue-rejecting polyamide (break-proof) with large, plane clamping surfaces for protective, parallel fixing without additions
- Clamping force up to 1,500 N
- Special product benefits:
 - The clamp tightens around the rail and, as a result, those clamp points become accessible which cannot be reached with usual screw clamps.
 - The end stop is removable tool-free for reversing the lower part (problem-free conversion to spreading function). Further technical information:



- Cross-section of rail: 20 x 5mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.