



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## BÖHLER ROD ELECTRODE BOEHLER FOX ETI E 42 0 RR 1 2 3.2 X 350 MM UNALLOYED

SKU: 4038588114761

Rod electrode BOEHLER FOX ETI E 42 0 RR 1 2  
3.2 x 350 mm unalloyed



Categories: [Filler materials](#), [Rod electrodes](#)

**Product Features:** Weight: 4.7 kg

Length: 350 mm

EN ISO: E 42 0 RR 1 2

Ø: 3.2 mm

Sheath: Rutile

Brand: BÖHLER

[safety instructions](#)

Scope of delivery:

4,70 KG Rod electrode BOEHLER FOX ETI E 42  
0 RR 1 2 3.2 x 350 mm unalloyed |

## PRODUCT DESCRIPTION

Standard designation: EN ISO 2560-A: E 42 0 RR 1 2 EN ISO 2560-B: E 4313 A AWS A5.1M: E4313 AWS A5.1 / SFA-5.1: E6013 Unalloyed

- Rutile coated Properties and area of application: Unsurpassed weldability in all positions with the exception of vertical-down seams

- Extremely smooth seams, self-releasing slag

- Low spatter and good AC welding properties

- Exceptional refiring properties and easy handling

- High extrusion lengths possible

- Versatile uses in Industry and trade Base materials: Steels up to a yield strength of 420 MPa (60ksi)

S235JR-S355JR, S235JO-S355JO, P195TR1-P265TR1, P195GH-P265GH, L245NB-L360NB, L245MB-L360MB, L415NB, L415MB, Shipbuilding steels: A, B, D ASTM A 106, Gr. A, B

- A 283 Gr. A, C

- A 285 Gr. A, B, C

- A 501, Gr. B

- A 573, Gr. 58, 65, 70

- A 633, Gr. A, C

- A 711 Gr. 1013



- API 5 L Gr. B, X42, X52, X60 Approvals: TÜV (01097 DB (10.014.102/01 ABS, BV, DNV GL, LR, CE Current type = + / ~
- Prices per kilogram Further technical information:
- Contents: 140 pc.
- Alloy: Unalloyed

#### **PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.