



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



BS ROLLEN SWIVEL CASTOR WHEEL DM 125 MM LOAD CAP. 200 KG WITH BOLT-ON PLATE CAST-POLYURETHANE BANDAGE

SKU: 4021885076214

Swivel castor wheel dm 125 mm load cap. 200 kg with bolt-on plate cast-polyurethane bandage

Categories: <u>Swivel castors</u>, <u>Wheels and</u> <u>Castors</u>

Product Features: Wheel Ø: 125 mm Width of wheel: 30 mm Overall height: 155 mm Load-bearing capacity: 200 kg Radius: 34 mm Material of castor: Cast polyurethane coating Attachment type: With screw-on plate Type: With

Scope of delivery: 1,00 ST Swivel castor wheel dm 125 mm load cap. 200 kg with bolt-on plate castpolyurethane bandage |

PRODUCT DESCRIPTION

Sheet steel casing, galvanised/chromated

- Two-rowed ball cage in fork head

- Die-cast polyurethane running surface, hardness 95 +/- 3 Shore, aluminium wheel body, high loadbearing capacity, minimal roll resistance, quiet running, excellent abrasion and tear strength, largely resistant to greases, oils, etc., operating temperature -20 °C / +80 °C

- Ball bearing
- With plate fitting
- Castors for heavy transporting Further technical information:
- Surface of housing: Galvanised/chromated
- Screw hole Ø: 9mm
- Screw hole removal: 80 x 55/60mm
- Supplement: Standard





- Width of panel: 85mm
- Material of housing: Sheet steel
- Length of panel: 115mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.