



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## BS ROLLEN SWIVEL CASTOR WHEEL DM 150 MM LOAD CAP. 550 KG WITH BOLT-ON PLATE CAST-POLYURETHANE BANDAGE

**SKU:** 4021885094126

Swivel castor wheel dm 150 mm load cap.  
550 kg with bolt-on plate cast-polyurethane  
bandage



**Categories:** [Swivel castors](#), [Wheels and Castors](#)

**Product Features:** Wheel Ø: 150 mm  
Width of wheel: 50 mm  
Overall height: 209 mm  
Load-bearing capacity: 550 kg  
Radius: 48 mm  
Material of castor: Cast polyurethane coating  
Attachment type: With screw-on plate  
Type: With

Scope of delivery:  
1,00 ST Swivel castor wheel dm 150 mm load  
cap. 550 kg with bolt-on plate cast-  
polyurethane bandage |

## PRODUCT DESCRIPTION

Sheet steel casing, galvanised/chromated

- Two-rowed ball cage in fork head
- Die-cast polyurethane running surface, hardness 95 +/- 3 Shore, aluminium wheel body, high load-bearing capacity, minimal roll resistance, quiet running, excellent abrasion and tear strength, largely resistant to greases, oils, etc., operating temperature -20 °C / +80 °C
- Ball bearing
- With plate fitting
- Castors for heavy transporting Further technical information:
- Surface of housing: Galvanised/chromated
- Screw hole Ø: 11mm
- Screw hole removal: 105 x 75mm
- Supplement: Standard



- Width of panel: 110mm
- Material of housing: Sheet steel
- Length of panel: 138mm

#### **PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.