



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



### **BS ROLLEN SWIVEL CASTOR WITH TOTAL STOP WHEEL DM 150 MM LOAD CAP. 250 KG WITH SCREW-ON PLATE BALL BEARINGS CAST-POLYURETHANE BANDAGE**

**SKU:** 4021885083588

Swivel castor with total stop wheel dm 150 mm load cap. 250 kg with screw-on plate ball bearings cast-polyurethane bandage

---

**Categories:** [Swivel castors with brakes,](#)  
[Wheels and Castors](#)

**Product Features:** Wheel Ø: 150 mm  
Width of wheel: 40 mm  
Overall height: 181 mm  
Load-bearing capacity: 250 kg  
Material of castor: Cast polyurethane coating  
Attachment type: With screw-on plate  
Type: Ball bearing  
Mark

Scope of delivery:  
1,00 ST Swivel castor with total stop wheel  
dm 150 mm load cap. 250 kg with screw-on  
plate ball bearings cast-polyurethane  
bandage |

## **PRODUCT DESCRIPTION**

Sheet steel housing

- Galvanised/chromated
- Two-rowed ball cage in fork head
- Die-cast polyurethane running surface, hardness 95 +/- 3 Shore, aluminium wheel body
- Minimal roll resistance
- Quiet running, excellent abrasion and tear strength, largely resistant to greases, oils, etc.
- Operating temperature -20 °C / +80 °C
- Wheel axle screwed
- Total stop mounted to precede wheel
- Ball bearing



- With plate fitting Further technical information:
- Surface of housing: Galvanised/chromated
- Screw hole Ø: 11mm
- Screw hole removal: 105 x 75/80mm
- Supplement: Standard
- Width of panel: 109mm
- Material of housing: Sheet steel
- Length of panel: 138mm
- Profile: Standard

#### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.