



### Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

# CONTINENTAL COMPRESSED AIR HOSE AIR TRIX® INTERNAL DM 25 MM EXTERNAL DM 39 MM LENGTH 40 M BLACK SBR

SKU: 4045998067648

Compressed air hose AIR TRIX® internal dm 25 mm external dm 39 mm length 40 m black SBR

**Categories:** <u>Hose Technology</u>, <u>Pressure and</u> <u>compressed air hoses</u>

### **Product Features:** External Ø: 39 mm Thickness of wall: 7 mm

Operating pressure: 10 bar Bending radius: 185 mm Bursting pressure: 40 bar Colour: Black Length: 40 m Temperature range: -40 to +85 °C Inner liner: SBR Out

Scope of delivery: 40,00 MT Compressed air hose AIR TRIX® internal dm 25 mm external dm 39 mm length 40 m black SBR |

## **PRODUCT DESCRIPTION**

The compressed air hose to EN ISO 2398-1A and DIN 20018-1

- Black, non-porous, smooth SBR inner layer

5 AIR TRIX\* DN 19 DIN EN ISO 2398:2017 1A / P

- Reinforcement: Synthetic yarns

- Black, smooth SBR outer layer, ozone, weather and UV-resistant, abrasion-resistant, resistant to non-potable water and oily air

- High flexibility, robustness, kink resistance and dimensional stability

- LABS, parting agent and grease free

- To EN ISO 2398:2010 1A and DIN 20018-1 Temperature range: -30 °C to +70 °C/-22°F to +158°F Labelling: 2x3 blue, axial stripes on black substrate "Continental AIR ContiTech TRIX® DN 19 EN ISO 2398:2010 1A / N-T DIN 20018-1 1.0 MPa (10 BAR/145 PSI) Made in Germany Areas of use: The reliable





specialist for heavy-duty use in quarries, building and civil engineering, for compressed air and compressor manufacturers, industrial loads, in the steelworks industry, shipyards, petrol stations and large garages. Also available in type to §10 BVOSt (formerly LOBA). Further technical information: - Weight: 1kg/m

#### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.