



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**CONTINENTAL COMPRESSED AIR
HOSE TRIX® BLAUSTRAHL INTERNAL
DM 19 MM EXTERNAL DM 29 MM
LENGTH 40 M BLUE/BLACK NBR**

SKU: 4045998018886



Compressed air hose TRIX® Blaustrahle internal dm 19 mm external dm 29 mm length 40 m blue/black NBR

Categories: [Hose Technology](#), [Pressure and compressed air hoses](#)

Product Features: External Ø: 29 mm
Thickness of wall: 5 mm
Operating pressure: 25 bar
Bending radius: 85 mm
Bursting pressure: 100 bar
Colour: Blue/black
Length: 40 m
Temperature range: -40 to +70 °C
Inner liner: NBR

Scope of delivery:
40,00 MT Compressed air hose TRIX®
Blaustrahle internal dm 19 mm external dm 29 mm length 40 m blue/black NBR |

PRODUCT DESCRIPTION

To DIN EN ISO 2398 : 2010 Type 3C / L-T

- Black, non-porous, smooth EDPM inner layer
- Reinforcement: Synthetic yarns
- NBR outer layer, insensitive to ozone, weather and UV radiation, abrasion-resistant
- Highly flexible and robust
- From DN 28 CR outer layer, material patterned
- Very good oil resistance, RMA Class A
- Length-independent electrically conductive, R 6
- From DN 25 LABS, parting agent and grease-free
- To DIN EN ISO 2398 3C/LT, from DN 28 2C/L-T Temperature range: -40 °C to +85 °C Labelling: 6 blue, axial stripes on black background, "ContiTech Continental TRIX® BLAUSTRAHL® DN 19 DiN EN ISO 2398 :



2010 3 C / L-T air/air 2.5 MPa (25 bar) R 6 /m Made in Germany" Areas of use: The TRIX®-Blaustrahl is the top-quality product for heavy-duty compressed air use. The hose conforms to the DIN EN ISO 2398 standard and is the top working equipment for industry, mining, quarries, building and civil engineering, steelworks industry, shipyards, compressed air equipment and compressor manufacturers, petrol stations, large garages and many other areas. LOBA (State Upper Mining Office) type on request. Further technical information:

- Weight: 0.59kg/m

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.