



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

FLUX-CORED WIRE DM 1.6 MM LOW ALLOY

SKU: 4251435516253

Flux-cored wire dm 1.6 mm low alloy



Categories: [Filler materials](#), [Flux-cored wires](#)

Product Features: Ø: 1.6 mm

Material: DT-RF 14

Scope of delivery:

16,00 KG Flux-cored wire dm 1.6 mm low alloy |

PRODUCT DESCRIPTION

Standard designation: EN ISO 17632-A: T 46 4 P M 1 H5 / T46 2 P C 1 H5 AWS A5.36: E71T1-M21A4-CS1-GH4 E71T1-C1A2-CS1-GH4 Properties and area of application: Low-alloy rutile flux-cored wire with fast freezing slag

- Suitable for welding in all positions
- Spatter-free, with very easy-to-remove slag
- Very good modelling capability Yield >85 % On 16 kg BS-300 basket-type reel Base materials: St 37.0 - St 52.0 HI / HII, 17 Mn 4 StE 255 - StE 460 TÜV sheet 1000: Group 1-4 ISO 20172: Group 1.1 ISO 20172: Group 1.2 Approvals: TÜV / DB Further technical information:
- Alloy: Low alloy
- Type: Rutile

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.