Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



HONGSHANG HEAT SHRINKABLE TUBE H-2(Z) FOR INTERNAL DM 1.60 MM SHRINK RATE 1.6/0.8 L 15 M BLACK

SKU: 8711278575889

Heat shrinkable tube H-2(Z) for internal dm 1.60 mm shrink rate 1.6/0.8 L 15 m black

---

Categories: Hose Technology, Shrink hoses

Product Features: for internal Ø: 1,60 mm
Shrink rate: 1,6/0,8
Min. shrink temperature: +70 °C
Length: 15 m
Min. temperature for comp. shrinkage: +100 °C
Colour: Black
Lowest temperature: -55 °C
Extreme temperature:

Scope of delivery:
1,00 ST Heat shrinkable tube H-2(Z) for internal dm 1.60 mm shrink rate 1.6/0.8 L 15 m black |

PRODUCT DESCRIPTION

Thin-walled heat shrinkable tube with a shrink rate of 2:1
- Operating temperature from -55 °C to +125 °C
- Min. shrinking temperature +70 °C
- Minimum temperature for complete shrinkage +100 °C
- Flame resistant
- Approvals: UL224 125 °C VW-1 600 V file E204071, CSA file no. 1934614
- Satisfies RoHS and Sony-SS-00259
- Black
- In practical unwind box

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you

Copyright © 2023 Actik Tools All rights reserved

verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools

All rights reserved