



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

HONGSHANG HEAT SHRINKABLE TUBE H-5(3X)-F FOR INTERNAL DM 40.00 MM SHRINK RATE 40.0/13.0 L 1.22 M BLACK

SKU: 8719956038471



Heat shrinkable tube H-5(3X)-F for internal dm 40.00 mm shrink rate 40.0/13.0 L 1.22 m black

Categories: [Hose Technology](#), [Shrink hoses](#)

Product Features: for internal \varnothing : 40,00 mm
Shrink rate: 40,0/13,0
Min. shrink temperature: +70 °C
Length: 1.22 m
Min. temperature for comp. shrinkage: +100 °C
Colour: Black
Lowest temperature: -55 °C
Extreme temperat

Scope of delivery:
5,00 ST Heat shrinkable tube H-5(3X)-F for internal dm 40.00 mm shrink rate 40.0/13.0 L 1.22 m black |

PRODUCT DESCRIPTION

Double-walled heat shrinkable tube with adhesive coating with a shrink rate of 3:1

- Excellent sealing and insulation properties
- UV-resistant
- As a bar 1.22 m long
- Black
- Operating temperature from -55 °C to +125 °C
- Min. shrinking temperature +70 °C
- Minimum temperature for complete shrinkage +110 °C
- Flame resistant
- Approvals: UL224 125 °C VW-1 600 V file E204071
- Satisfies RoHS and SAE-AMS-DTL-23053/4



PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.