



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

MARSTON UNIVERSAL SEALING COMPOUND RED 20 G

SKU: 4016673008768

Universal sealing compound red 20 g



Categories: [Chemical-technical products](#), [Surface, pipe and screw thread seals](#)

Product Features: Contents: 20 g

Container: Tube

Thermal resistance: -55 to +270 °C

Brand: MARSTON

Approval: DVGW, NSF P1

[safety instructions](#)

Scope of delivery:

10,00 ST Universal sealing compound red 20 g |

PRODUCT DESCRIPTION

Non-hardening

- Very good adhesion on the sealing surface (adhesion)
- For material combinations: Metal-metal, metal-plastic, plastic-plastic
- Temperature-resistant from -55 °C to +270 °C, short-term up to +300 °C
- Full load capacity after 15 min
- Resistant to many mineral oils and a large number of synthetic oils, lubricants, propellants, additives, air, gases, water and water antifreeze mixtures
- Can be used universally for many different seals
- Easy to dismantle
- DVGW approval - NSF approval (drinking water) P1 (Reg. No. 146099) Further technical information:
- Gap filling capacity: Max. 0.2mm
- Colour: Red
- Viscosity: Pasty

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.