



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



OPTI-DRILL BENCH DRILL B 24 H 24 (S235JR) MM MK2 350-4,000 MIN-1 W. EMERGENCY STOP SWITCH

SKU: 4030635010729

Bench drill B 24 H 24 (S235JR) mm MK2 350-4,000 min-1 w. emergency stop switch

Categories: Bench drills, Metal processing

Product Features: Drilling power: 24

(S235JR) mm

Spindle mounting: MK2 Spindle stroke: 85 mm

Radius: 165 mm No. of steps: 7

Spindle revolutions: 350-4000 min-1 Mains voltage: 400 V / 50 Hz

Width: 434 mm Length: 665

Scope of delivery: 1,00 ST Bench drill B 24 H 24 (S235JR) mm MK2 350-4,000 min-1 w. emergency stop

switch |

PRODUCT DESCRIPTION

Concentricity better than 0.015 mm (measured in the barrel)

- Spindle with precision ball bearings
- Aluminium belt pulleys
- Belt cover with safety switch
- V-belt tensioning device
- Drill depth stop
- Separate emergency stop shock switch
- Drilling table can be rotated through 360° with diagonal 14 mm T-grooves
- Die-cast aluminium sleeve levers with soft-grip support
- Height-adjustable visor with safety switch Further technical information:
- Weight: 92kg
- Column Ø: 80mm
- Clamping surface: 280 x 300mm





- Size of T-slot: 14mm- Engine power: 0.85kW- Subject to audit: Yes

- Type: With emergency stop switch Scope of supply: Quick-clamp drill chuck (1-16 mm) B16, tapered mandrel MK2 B16, T-sliding blocks, machinery light

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.