



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

OPTI-DRILL BENCH DRILL DX 17 V 16 (S235JR) MM M8 (S235JR) MK2 50-4,000 MIN⁻¹

SKU: 4030635035982

Bench drill DX 17 V 16 (S235JR) mm M8 (S235JR) MK2 50-4,000 min⁻¹



Categories: [Bench drills](#), [Metal processing](#)

Product Features: Drilling power: 16 (S235JR) mm
Continuous drilling capacity: 13 (S235JR) mm
Thread cutting capacity: M8 (S235JR)
Spindle mounting: MK2
Spindle stroke: 60 mm
Radius: 235 mm
No. of steps: Electronic c

Scope of delivery:
1,00 ST Bench drill DX 17 V 16 (S235JR) mm
M8 (S235JR) MK2 50-4,000 min⁻¹ |

PRODUCT DESCRIPTION

Continuously adjustable rev regulation with potentiometer and digital LCD display

- Aluminium belt pulleys
 - Emergency stop shock switch
 - Height adjustable chuck guard with micro-switch
 - Drill spindle with precision ball bearings
 - Glare-free LED lighting integrated to the left and right of the drill head
 - Dirt- and water-resistant, easy-to-clean membrane keypad with OLED display
 - Pivoted drilling table with parallel T-slots - digital reference point
 - Digital part counter
 - Acoustic signal when drilling depth is reached
 - Thread cutting mode
- Further technical information:
- Weight: 73kg
 - Column Ø: 60mm
 - Size of T-slot: 10mm
 - Clamping surface: 290 x 290mm
 - Engine power: 1.0kW



- Subject to audit: Yes Scope of supply: Quick-clamp drill chuck 1-13 mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.