



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



**PFERD ROUND BRUSH RBG 11512/22.2
CT ST 0.50 DM 115 MM WIRE
THICKNESS 0.5 MM STEEL 12 MM
12500 MIN⁻¹**

SKU: 4007220593356

1,00 ST Round brush RBG 11512/22.2 CT ST
0.50 dm 115 mm wire thickness 0.5 mm steel
12 mm 12500 min⁻¹

Categories: [Machine brushes](#), [Wire Brushes](#)

Product Features: Ø: 115 mm
Width of lining: 12 mm
Thickness of wire: 0.5 mm
No. of braids: 24
Max. revolutions: 12500 min⁻¹
Mount: 22.2 mm
Material qualification cast: Very suitable
Bore: 22.2 mm
Material qualificat

Scope of delivery:
1,00 ST Round brush RBG 11512/22.2 CT ST
0.50 dm 115 mm wire thickness 0.5 mm steel
12 mm 12500 min⁻¹ |

PRODUCT DESCRIPTION

COMBITWIST braiding

- Very aggressive brush
- Suitable for tough brushing work in metal constructions, such as descaling, rust removal, deburring, cleaning weld seams and removing adhesive residues
- High service life and material abrasion
- Very convenient to work with thanks to the smooth operation without recoil of the brush
- Suitable for machining corners and edges as the braids do not open as much
- Bore 22.2 mm Ø

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the



product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.