



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



**PFERD ROUND BRUSH RBG 12512/22.2  
ST 0.50 DM 125 MM WIRE THICKNESS  
0.5 MM STEEL 12 MM 12500 MIN-<sup>1</sup>  
MAX. REVOLUTIONS 12500 MIN-<sup>1</sup>**

**SKU:** 4007220952702

1,00 ST Round brush RBG 12512/22.2 ST 0.50  
dm 125 mm wire thickness 0.5 mm steel 12  
mm 12500 min-<sup>1</sup> Max. revolutions 12500 min-  
<sup>1</sup>

---

**Categories:** [Machine brushes](#), [Wire Brushes](#)

**Product Features:** Ø: 125 mm  
Width of lining: 12 mm  
Thickness of wire: 0.5 mm  
No. of braids: 24  
Max. revolutions: 12500 min-<sup>1</sup>  
Material qualification cast: Very suitable  
Bore: 22.2 mm  
Material qualification steel: Very

Scope of delivery:  
1,00 ST Round brush RBG 12512/22.2 ST 0.50  
dm 125 mm wire thickness 0.5 mm steel 12  
mm 12500 min-<sup>1</sup> Max. revolutions 12500 min-  
<sup>1</sup> |

## PRODUCT DESCRIPTION

Braided wire

- Aggressive brush
- Suitable for tough brushing work in metal constructions, such as descaling, rust removal, deburring, cleaning weld seams and removing adhesive residues
- Bore 22.2 mm Ø

## PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.