



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PONAL WOOD GLUE EXPRESS 550 G EN 204: D1, D2

SKU: 4015000071994

Wood glue Express 550 g EN 204: D1, D2



Categories: [Chemical-technical products](#),
[Glues and accessories](#)

Product Features: Contents: 550 g

Container: Bottle

Type: PN10X

Brand: PONAL

Stress group: EN 204: D1, D2

[safety instructions](#)

Scope of delivery:

10,00 ST Wood glue Express 550 g EN 204:
D1, D2 |

PRODUCT DESCRIPTION

PVAC glue with short setting time

- For bonding wood and wood-based panels
- For assembly glueing, gluing joints, carcass bonding, dowels, mortise and tenon
- For bonding solid wood edging in corners, as well as for surface bonding of laminates (HPL) on wood based panels
- Suitable for handicrafts Further technical information:
- Processing temperature: Not below +7°C
- Wet life of glue: Max. 8min.
- Thermal resistance: Up to +70 °C
- Consumption: Approx. 150 g/m²

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.