Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT CHEMICALS 2-COMPONENT INSTALLATION FOAM 400 ML B2 LIGHT-GREEN WITH DISPOSABLE GLOVES WITH DISPOSABLE GLOVES

SKU: 4015448716891

2-component installation foam 400 ml B2 light-green with disposable gloves with disposable gloves

---

Categories: Chemical-technical products, Fillers

Product Features: Contents: 400 ml
Colour: Light green
Construction material class: B2
Brand: PROMAT CHEMICALS
Foam yield: Up to 9.3 l
Supply: With disposable gloves
Datasheet

Scope of delivery:
12,00 ST 2-component installation foam 400 ml B2 light-green with disposable gloves with disposable gloves |

PRODUCT DESCRIPTION

B2 to DIN 4102 part 1
- Two-component, ready to use, self-expanding polyurethane fast acting foam with excellent dimensional stability
- Hardens independently of humidity
- Can be cut after only 13 minutes
- Very low emissions - EC1R PLUS licensed
- For the installation and insulation of door frames, wooden door linings and window elements to EnEV, DIN 4108-7 and RAL assembly guidelines
- Installation of DIN-tested window sills and stairway steps, for the setting of bathtub and shower tray supports, foaming of difficult to access and poorly ventilated cavities
- Adheres on almost all substrates, except for PE, PP, PTFE, silicone
- Resistant to a large number of solvents, paints, chemicals, oil and petrol
- Ageing resistant

Copyright © 2023 Actik Tools All rights reserved

- Not UV-resistant
- Not suitable for continuous use under water
- Foam yield: Up to 9.3 litres
- Can contents sufficient for up to 2 door frames
- Thermal resistance:-40 °C to +90 °C
- Processing temperature: Contact surface and environment +5 °C to +35 °C/can +5 °C to +30 °C
- Silicone-free Further technical information:
- Durability: 15 months
- Chemical basis: Polyurethane
- Processing temperature: +5 to +35°C
- Temperature range: -40 to +90°C
- Container: Can Disposal information: Used PU foam cans are considered hazardous waste and cannot be disposed of in household waste, yellow sacks, building rubble or tinplate containers. Individual cans must be deposited at municipal special waste collection depots (www.pdr.de/plz-suche). Free collection by PDR Recycling GmbH + Co KG can be requested from a quantity of more than 6 boxes. Tel.: 0800 7836736. You can find more information at www.pdr.de.

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved