



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT CHEMICALS BUSHING/BEARING ADHESIVE HIGH STRENGTH, MEDIUM VISCOSITY GREEN 50 G

SKU: 4015448472902

Bushing/bearing adhesive high strength,
medium viscosity green 50 g

Categories: [Chemical-technical products](#),
[Surface, pipe and screw thread seals](#)

Product Features: Gap filling capacity: 0.15
mm

Strength class: High-strength

Viscosity: Medium-viscosity

Brand: PROMAT CHEMICALS

Thread: Max. M20

Scope of delivery:

1,00 ST Bushing/bearing adhesive high
strength, medium viscosity green 50 g |

PRODUCT DESCRIPTION

High-strength, medium-viscosity

- A 1-component anaerobic liquid plastic, cures on contact with metals when air is excluded
- Viscosity: 500 mPas (25 °C)
- Gap filling capacity: 0.15 mm
- Max. thread: M20
- Strength class 3 to DIN 30661
- Breakaway torque: 30 to 35 Nm
- Temperature-resistant from -55 °C to +175 °C
- Handling strength after approx. 2 to 5 min.
- Functional strength after 1 to 3 hours
- Ideally suitable for fixing bearings on shafts or bearing housings
- Fast curing
- Resistant to various oils, petrol, brake fluid and other substances
- Very high strength, even when parts to be joined are slightly oily
- Can be used in engine construction, the automotive and motorcycle industries, the electrical industry, mechanical engineering, mining, the food industry and turbine and nuclear power stations



- Can be used in engine construction, the automotive and motorcycle industries, the electrical industry, mechanical engineering, mining, the food industry and turbine and nuclear power stations Further technical information:

- Contents: 50g
- Colour: Green
- Breakaway torque: 30 to 35Nm
- Thermal resistance: -55 °C to +175 °C
- Container: Bottle

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.