



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## PROMAT CHEMICALS HIGH- PERFORMANCE COOLING LUBRICANT WATER-MISCIBLE 5 L



**SKU:** 4015448551805

High-performance cooling lubricant water-miscible 5 l

---

**Categories:** [Chemical-technical products](#),  
[Cutting agents](#)

**Product Features:** Contents: 5 l

Brand: PROMAT CHEMICALS

Scope of delivery:

1,00 ST High-performance cooling lubricant  
water-miscible 5 l |

### PRODUCT DESCRIPTION

#### Water-miscible

- With effective EP additives, causes a substantial extension in tool service life and enables machining with high cutting speeds
- Long-term stability
- Excellent corrosion protection
- Dermatologically tested
- Is used in different various chip removal processes
- Density/20 °C: 915 kg/m<sup>3</sup> (DIN EN ISO 12185)
- Viscosity/40 °C: 30-45 mm<sup>2</sup>/s (DIN EN ISO 3104)
- PH value (4-5 %): 9.2 (DIN 51 369)
- Cast iron chips test: 0 [1:20] (DIN 51 360/T 2)
- Mineral oil content: 62.5 %
- Recommended storage temperature: +5 °C to max. +40 °C
- Concentration used: Drilling/milling etc.: 1:20 Grinding/sawing etc.: 1:10 Thread cutting: 1:5 to 1:10

Further technical information:

- Colour: Yellow
- Type: Water-miscible
- Container: Canister

### PRODUCT DATASHEET LEGAL NOTE



Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.