



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT CHEMICALS INSTANT ADHESIVE FOR EXTREME LOADS FÜR EXTREME BELASTUNGEN 20 G COLOURLESS

SKU: 4015448551188

Instant adhesive for extreme loads für extreme Belastungen 20 g colourless

Categories: Chemical-technical products, Instant adhesives

Product Features: Contents: 20 g

Container: Bottle Colour: Colourless

Viscosity: 2,500-3,000 mPa.s Brand: PROMAT CHEMICALS Thermal resistance: -50 to +135 °C

Scope of delivery:

1,00 ST Instant adhesive for extreme loads für extreme Belastungen 20 g colourless

PRODUCT DESCRIPTION

Special cyanoacrylate adhesive for special loads, 6-times higher impact resistance and 10-times higher peel strength of conventional CA adhesives

- Very high tensile shear strength (240 kg per square cm in a steel/steel bond)
- Thermal resistance up to \pm 135 °C (at this high load the adhesive still has a tensile shear strength of 60 kg per square cm in a steel/steel bond)
- Very good water resistance
- Particularly suitable for steel, plastic, glass and ceramic
- Viscosity: 2,500 to 3,000 mPas (20 °C)
- Gap filling capacity: 0.15 mm
- Handling strength after: Aluminium: 30-50 seconds, rubber: 20-40 seconds
- Temperature-resistant from 50 °C to + 135 °C
- Can be used in the electrical and electronics industries, mechanical engineering, metalworking, car assembly, plastics processing, model making, furniture industry, etc. Further technical information:
- Max. gap bridging: 0,15mm





PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved