



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



SKU: 4015448742913

Countersink DIN 334 C 60 deg nominal diameter 6.3 mm HSS Z.3

Categories: Countersink drill bit sand deburrers, Countersink drill bits

Product Features: Coating: Uncoated

Nominal Ø: 6.3 mm Small Ø: 1.6 mm Shank Ø: 5 mm

Overall length: 45 mm Countersink angle: 60 °

No. of cutters: 3 Standard: DIN 334 C Cutting material: HSS Brand: PROMAT

Scope of delivery: 1,00 ST Countersink DIN 334 C 60 deg nominal diameter 6.3 mm HSS Z.3 |



PRODUCT DESCRIPTION

HSS

- DIN 334 C
- 3 cutters
- Countersink angle 60°
- Straight shank
- Right-hand cutting
- Ideal for burr-free and chatter-free countersinking, deburring, and countersinking in steel and cast iron as well as non-ferrous and light metals
- Best results at low cutting speed Further technical information:
- Feed in steel up to 500 N: 0,09mm/rev

PRODUCT DATASHEET LEGAL NOTE





Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved