



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT COUNTERSINK DIN 335 C 90 DEG NOMINAL DIAMETER 10.4 MM ASP Z.3

SKU: 4015448547525

Countersink DIN 335 C 90 deg nominal diameter 10.4 mm ASP Z.3



Categories: [Countersink drill bit sand deburrers](#), [Countersink drill bits](#)

Product Features: Coating: Uncoated

Nominal Ø: 10.4 mm

Small Ø: 2.5 mm

Shank Ø: 6 mm

Overall length: 50 mm

Type: Stainless steel

Countersink angle: 90 °

No. of cutters: 3

Standard: DIN 335 C

Cutting material: ASP

Scope of delivery:

1,00 ST Countersink DIN 335 C 90 deg nominal diameter 10.4 mm ASP Z.3 |

PRODUCT DESCRIPTION

Powder steel

- ASP
- DIN 335 C
- For VA steels and non-ferrous metals
- 3 cutters
- Countersink angle 90°
- Straight shank
- For countersinking and deburring bores
- ASP Countersink drill bit sand deburrer made of powder metallurgical high-speed steel
- Unlike conventional HSS steels, metallurgically produced steels have a uniform, fine-grained material structure
- They therefore have a good warm hardness, compressive strength, and wear resistance



- Ideal for VA steels, rust-, and acid- resistant steels as well as titanium and titanium alloys Further technical information:

- Feed in steel up to 500 N: 0,12mm/rev

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.