



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**PROMAT END MILL DIN 6527 L TYPE  
NF NOMINAL DIAMETER 10 MM VHM  
TiAlN 45 DEG DIN 6535 HB NO. OF  
CUTTERS 4 LONG**

**SKU:** 4015448546252



End mill DIN 6527 L type NF nominal  
diameter 10 mm VHM TiAlN 45 deg DIN 6535  
HB no. of cutters 4 long

---

**Categories:** [End mills](#), [Milling tools](#)

**Product Features:** Nominal Ø: 10 mm

Length of cutting edge: 22 mm

Overall length: 72 mm

Shank Ø: 10 mm

No. of cutters: 4

Shank design: DIN 6535 HB

Type: NF

Coating: TiAlN-coated

Standard: DIN 6527 L

Cutting materia

Scope of delivery:

1,00 ST End mill DIN 6527 L type NF nominal  
diameter 10 mm VHM TiAlN 45 deg DIN 6535

HB no. of cutters 4 long |

## PRODUCT DESCRIPTION

With chip cuttings divider and unequal partition

- Solid carbide
- TiAlN-coated
- DIN 6527 L
- Type NF
- Four-tipped core drill
- Long
- With straight shank in accordance with DIN 6535 HB
- 45 degree angle of twist
- Product advantages: Highest stability of the tool thanks to the special configuration of the cutter geometry, universal application , ideally suited for roughing or finishing with outstanding quality of finish,



(multi-layer TiAlN coating) with optimum protection against wear and temperature stability Further technical information:

- Material qualification INOX stainless steel: Very suitable
- Material qualification cast: Somewhat suitable
- Angle of twist: 45°
- Material qualification steel: Very suitable
- Material qualification of special alloys: Somewhat suitable
- Material qualification NF metals: Somewhat suitable

#### **PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.