



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**PROMAT END MILL DIN 6527 L TYPE  
NR NOMINAL DM 14 MM INSERT  
LENGTH 35 MM VHM TiAlN DIN 6535  
HB NO. OF CUTTERS 4 LONG**

**SKU:** 4015448567219



End mill DIN 6527 L type NR nominal dm 14 mm insert length 35 mm VHM TiAlN DIN 6535 HB no. of cutters 4 long

---

**Categories:** [End mills](#), [Milling tools](#)

**Product Features:** Nominal Ø: 14 mm

Length of cutting edge: 26 mm

Overall length: 83 mm

Length of insert: 35 mm

Shank Ø: 14 mm

Free grinding: 13,6 mm

No. of cutters: 4

Shank design: DIN 6535 HB

Type: NR

Coating: TiAl

[Datasheet](#)

Scope of delivery:

1,00 ST End mill DIN 6527 L type NR nominal dm 14 mm insert length 35 mm VHM TiAlN DIN 6535 HB no. of cutters 4 long |

## PRODUCT DESCRIPTION

Solid carbide

- Universal finest grain
- TiAlN-coated
- DIN 6527 L
- Type NR
- Four-tipped core drill
- Long
- 45° protective chamfer
- With straight shank in accordance with DIN 6535 HB
- 45° angle of twist



- Right-hand cutting
- Neck free grinding
- Positive clamping angle for higher flexibility of use
- Cutting design with special roughing profile
- Enables low-vibration processing Further technical information:
- Shank tolerance: h6
- Material qualification INOX stainless steel: Somewhat suitable
- Material qualification cast: Very suitable
- Angle of twist: 45°
- Material qualification steel: Very suitable
- Material qualification of special alloys: Somewhat suitable
- Material qualification NF metals: Very suitable

#### **PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.