



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**PROMAT END MILL FACTORY  
STANDARD NOMINAL DM 20 MM  
INSERT LENGTH 75 MM VHM TIALN  
DIN 6535 HB NO. OF CUTTERS 5 EXTRA  
LONG**

**SKU:** 4015448717119



End mill factory standard nominal dm 20 mm  
insert length 75 mm VHM TiAlN DIN 6535 HB  
no. of cutters 5 extra long

---

**Categories:** [End mills](#), [Milling tools](#)

**Product Features:** Nominal Ø: 20 mm  
Length of cutting edge: 60 mm  
Overall length: 130 mm  
Length of insert: 75 mm  
Shank Ø: 20 mm  
Free grinding: 19,5 mm  
No. of cutters: 5  
Shank design: DIN 6535 HB  
Coating: TiAlN-coated

Scope of delivery:  
1,00 ST End mill factory standard nominal dm  
20 mm insert length 75 mm VHM TiAlN DIN  
6535 HB no. of cutters 5 extra long |

## PRODUCT DESCRIPTION

- Solid carbide
- Universal finest grain
  - TiAlN-coated
  - Factory standard
  - Type N
  - Multiple cutter
  - Extra long
  - 3xdiam. length of cutting edge
  - 45° protective chamfer
  - Centre cut
  - With straight shank in accordance with DIN 6535 HB



- Unequal pitch
- Right-hand cutting
- Neck free grinding
- For low-vibration processing, suitable for roughing and finishing
- As a result of newly developed geometry and coating, can be used universally for milling in steel, cast steel, grey cast iron, malleable cast iron, Cr-Ni steels, non-ferrous metals, aluminium with silicon content, and abrasive materials Further technical information:
- Shank tolerance: h6
- Material qualification INOX stainless steel: Very suitable
- Material qualification cast: Very suitable
- Material qualification steel: Very suitable
- Protective chamfer: 0.3mm
- Material qualification of special alloys: Very suitable
- Material qualification NF metals: Very suitable

#### **PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.