



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

**PROMAT FULL RADIUS MILLING TOOL  
FACTORY STANDARD NOMINAL DM 3  
MM INSERT LENGTH 9 MM VHM TIALN  
DIN 6535 HB NO. OF CUTTERS 2  
SHORT**

**SKU:** 4015448717133



Full radius milling tool factory standard nominal dm 3 mm insert length 9 mm VHM TiAlN DIN 6535 HB no. of cutters 2 short

---

**Categories:** [Milling tools](#), [Radius cutter](#)

**Product Features:** Nominal Ø: 3 mm

Radius: 1.5 mm

Length of cutting edge: 5 mm

Overall length: 50 mm

Length of insert: 9 mm

Shank Ø: 6 mm

Free grinding: 2,9 mm

No. of cutters: 2

Shank design: DIN 6535 HB

Type: N

Coat

Scope of delivery:

1,00 ST Full radius milling tool factory standard nominal dm 3 mm insert length 9 mm VHM TiAlN DIN 6535 HB no. of cutters 2 short |

## PRODUCT DESCRIPTION

Solid carbide

- Universal finest grain
- TiAlN-coated
- Factory standard
- Type N
- Two-flute cutter
- Short
- Centre cut



- With straight shank in accordance with DIN 6535 HB
- 30 degree angle of twist
- Right-hand cutting
- For milling steel and cast steel, grey cast iron, annealed cast iron, Cr/Ni steels, bronze, brass, copper, aluminium with silicon content, and abrasive plastics
- for milling steel and cast steel, grey cast iron, annealed cast iron, Cr-Ni steels, bronze, brass, copper, aluminium with silicon content, and abrasive plastics Further technical information:
- Shank tolerance: h6
- Material qualification INOX stainless steel: Very suitable
- Material qualification cast: Very suitable
- Angle of twist: 30°
- Material qualification steel: Very suitable
- Material qualification of special alloys: Very suitable
- Material qualification NF metals: Very suitable

#### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.