



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT INSERT DCGT11T304-AL N20 ALUMINIUM MACHINING

SKU: 4015448510383

Insert DCGT11T304-AL N20 aluminium machining

Categories: Indexable insert tools, Interchangeable cutting inserts

Product Features: Coating: Uncoated, highly

polished

ISO designation: DCGT11T304-AL

Type: N20

WSP: DCGT 11T3 Brand: PROMAT

Datasheet
Datasheet
Datasheet

Datasheet

Scope of delivery: 10,00 ST Insert DCGT11T304-AL N20 aluminium machining |

PRODUCT DESCRIPTION

For the processing of aluminium Further technical information:

- d: 9.525mm
- Area of application: Aluminium processing
- r: 0.4mm
- d1: 4.4mm
- s: 3,97mm
- I: 11,6mm
- Max. feed rate: mm/rev in steel / mm/rev in stainless steel / mm/rev in cast / 0.24 mm/rev in NI metals / mm/rev in superalloys / mm/rev in hardened steels
- Vc max.: m/min in steel / m/min in stainless / m/min in cast / 490 m/min in NI metals / m/min in superalloys / m/min in hardened steels
- Vc min.: m/min in steel / m/min in stainless / m/min in cast / 120 m/min in NI metals / m/min in superalloys / m/min in hardened steels
- Min. cutting depth: mm in steel / mm in stainless / mm in cast / 0.4 mm in NI metals / mm in





All rights reserved

superalloys / - mm in hardened steels

- Max. cutting depth: mm in steel / mm in stainless / mm in cast / 3.3 mm in NI metals / mm in superalloys / mm in hardened steels
- Min. feed rate: mm/rev in steel / mm/rev in stainless steel / mm/rev in cast / 0.1 mm/rev in NI metals / mm/rev in superalloys / mm/rev in hardened steels

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.