



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## PROMAT INSERT DNMG150612-R PMK30 ROUGH MACHINING

**SKU:** 4015448511106

Insert DNMG150612-R PMK30 rough machining

**Categories:** <u>Indexable insert tools</u>, <u>Interchangeable cutting inserts</u>

Product Features: Coating: TiAlN-coated ISO designation: DNMG150612-R Type: PMK30 WSP: DNMG 1506 Brand: PROMAT Datasheet Datasheet Datasheet Datasheet

Scope of delivery: 10,00 ST Insert DNMG150612-R PMK30 rough machining |

## **PRODUCT DESCRIPTION**

For roughing = R Further technical information:

- d: 12.7mm
- Area of application: Rough processing
- r: 1.2mm
- d1: 5.16mm
- s: 6,35mm
- l: 15,5mm

- Max. feed rate: 0.7 mm/rev in steel / 0.53 mm/rev in stainless steel / 0.7 mm/rev in cast / - mm/rev in NI metals / 0.42 mm/rev in superalloys / - mm/rev in hardened steels

- Vc max.: 235 m/min in steel / 140 m/min in stainless / 220 m/min in cast / - m/min in NI metals / 70 m/min in superalloys / - m/min in hardened steels

- Vc min.: 185 m/min in steel / 110 m/min in stainless / 175 m/min in cast / - m/min in NI metals / 35 m/min in superalloys / - m/min in hardened steels

- Min. cutting depth: 1.5 mm in steel / 1.5 mm in stainless / 1.5 mm in cast / - mm in NI metals / 1.5 mm in superalloys / - mm in hardened steels







Max. cutting depth: 4.5 mm in steel / 3.4 mm in stainless / 4.5 mm in cast / - mm in NI metals / 2.7 mm in superalloys / - mm in hardened steels
Min. feed rate: 0.25 mm/rev in steel / 0.25 mm/rev in stainless steel / 0.25 mm/rev in cast / - mm/rev in NI metals / 0.25 mm/rev in superalloys / - mm/rev in hardened steels

## PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.