



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## PROMAT MACHINE TAP DIN 376C GG M18 X 2.5 MM HSS-CO TiCN 6HX

**SKU:** 4015448526216

Machine tap DIN 376C GG M18 x 2.5 mm  
HSS-Co TiCN 6HX



**Categories:** [Machine taps](#), [Threaded Tools](#)

**Product Features:** Standard: DIN 376

Nominal thread Ø: M18

Pitch: 2,5 mm

Overall length: 125 mm

Thread length: 34 mm

Square: 11 mm

Core hole Ø: 15,5 mm

Type: GG

Coating: TiCN-coated

Shape: C

Tolerance range: 6HX

C

Scope of delivery:

1,00 ST Machine tap DIN 376C GG M18 x 2.5  
mm HSS-Co TiCN 6HX |

## PRODUCT DESCRIPTION

HSS-Co

- Shape C

- Type GG

- TiCN-coated

- White ring

- Straight-fluted

- Flanks relief-ground

- Metric ISO thread

- DIN 13 Sheet 1

- Tolerance range 6HX

- For through-hole and blind-hole threads

- For grey cast iron, graphite castings, malleable cast iron Further technical information:



- Shank Ø: 14mm

**PRODUCT DATASHEET LEGAL NOTE**

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.