



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT MACHINE TAP DIN 376C GG M20 X 2.5 MM HSS-CO TiCN 6HX

SKU: 4015448526223

Machine tap DIN 376C GG M20 x 2.5 mm
HSS-Co TiCN 6HX



Categories: [Machine taps](#), [Threaded Tools](#)

Product Features: Standard: DIN 376

Nominal thread Ø: M20

Pitch: 2,5 mm

Overall length: 140 mm

Thread length: 34 mm

Square: 12 mm

Core hole Ø: 17,5 mm

Type: GG

Coating: TiCN-coated

Shape: C

Tolerance range: 6HX

C

Scope of delivery:

1,00 ST Machine tap DIN 376C GG M20 x 2.5
mm HSS-Co TiCN 6HX |

PRODUCT DESCRIPTION

HSS-Co

- Shape C
- Type GG
- TiCN-coated
- White ring
- Straight-fluted
- Flanks relief-ground
- Metric ISO thread
- DIN 13 Sheet 1
- Tolerance range 6HX
- For through-hole and blind-hole threads
- For grey cast iron, graphite castings, malleable cast iron Further technical information:



- Shank Ø: 16mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.