



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT MACHINE TAP DIN 376C VA M18 X 2.5 MM HSS-CO NITRIDED AND VAPORISED 6H

SKU: 4015448523000

Machine tap DIN 376C VA M18 x 2.5 mm HSS-Co nitrided and vaporised 6H



Categories: [Machine taps](#), [Threaded Tools](#)

Product Features: Standard: DIN 376

Nominal thread Ø: M18

Pitch: 2,5 mm

Overall length: 125 mm

Thread length: 30 mm

Square: 11 mm

Core hole Ø: 15,5 mm

Type: VA

Coating: Nitrated and steam-tempered

Shape: C

Toleran

Scope of delivery:

1,00 ST Machine tap DIN 376C VA M18 x 2.5 mm HSS-Co nitrided and vaporised 6H |

PRODUCT DESCRIPTION

HSS-Co

- Shape C
- Type VA
- Nitrated and steam-tempered
- Blue ring
- With 40° right twist
- Flanks relief-ground
- Metric ISO thread
- DIN 13 Sheet 1
- Tolerance range ISO2 (6H)
- For blind hole threads
- For rust-, acid-, and heat-resistant steels up to 1,000 N/mm² in strength Further technical information:



- Shank Ø: 14mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.