



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT MACHINE TAP DIN 5156B VA G 3/8 INCH X19 HSS-CO VAPORISED ISO 228

SKU: 4015448609728

Machine tap DIN 5156B VA G 3/8 inch x19
HSS-Co vaporised ISO 228



Categories: [Machine taps](#), [Threaded Tools](#)

Product Features: Standard: DIN 5156
Nominal thread Ø: G 3/8
Overall length: 100 mm
Thread length: 21 mm
Square: 9 mm
Core hole Ø: 15,25 mm
Type: VA
Coating: Nitrated and steam-tempered
Shape: B
Tolerance range:

Scope of delivery:
1,00 ST Machine tap DIN 5156B VA G 3/8 inch
x19 HSS-Co vaporised ISO 228 |

PRODUCT DESCRIPTION

HSS-Co

- Shape B
- Type VA
- Nitrated and steam-tempered
- Blue ring
- Straight-fluted
- Flanks relief-ground
- Whitworth pipe thread G
- According to DIN ISO 228
- For through-hole threads
- For steels that are difficult to machine, e.g. rust-, acid-, and heat-resistant steels up to 1,000 N/mm² in strength Further technical information:
- Quality of finish: Steam-tempered
- Gg/1: 19



- Shank Ø: 12mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.