



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT MACHINE TAP DIN 5156C G 1/8 INCH X 28 HSS-CO ISO 228

SKU: 4015448523413

Machine tap DIN 5156C G 1/8 inch x 28 HSS-Co ISO 228

Categories: Machine taps, Threaded Tools

Product Features: Standard: DIN 5156 Nominal thread Ø: G 1/8 Overall length: 90 mm Thread length: 20 mm Square: 5.5 mm Core hole Ø: 8,8 mm Shape: C Tolerance range: ISO 228 Cutting material: HSS-Co Type of thread

Scope of delivery: 1,00 ST Machine tap DIN 5156C G 1/8 inch x 28 HSS-Co ISO 228 |

PRODUCT DESCRIPTION

PROMAT

HSS-Co

- Shape C
- With 40° right twist
- Flanks relief-ground
- Whitworth pipe thread G
- According to DIN ISO 228
- For blind hole threads
- In steels up to approx. 1,000 N/mm² strength and in annealed cast iron Further technical information:
- Gg/1: 28
- Shank Ø: 7mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you





verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.