



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

PROMAT MACHINE TAP DIN 5156C VA G 1/2 INCH X14 HSS-CO VAPORISED ISO 228

SKU: 4015448610083

Machine tap DIN 5156C VA G 1/2 inch x14
HSS-Co vaporised ISO 228



Categories: [Machine taps](#), [Threaded Tools](#)

Product Features: Standard: DIN 5156

Nominal thread Ø: G 1/2

Overall length: 125 mm

Thread length: 20 mm

Square: 12 mm

Core hole Ø: 19 mm

Type: VA

Coating: Nitrated and steam-tempered

Shape: C

Tolerance range: IS

Scope of delivery:

1,00 ST Machine tap DIN 5156C VA G 1/2 inch
x14 HSS-Co vaporised ISO 228 |

PRODUCT DESCRIPTION

HSS-Co

- Shape C
- Type VA
- Nitrated and steam-tempered
- Blue ring
- With 40° right twist
- Flanks relief-ground
- Whitworth pipe thread G
- According to DIN ISO 228
- For blind hole threads
- For steels that are difficult to machine, e.g. rust-, acid-, and heat-resistant steels up to 1,000 N/mm² in strength Further technical information:
- Quality of finish: Steam-tempered
- Gg/1: 14



- Shank Ø: 16mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.