



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT PUSHBUTTON-SAFETY COUPLING DN 7.4, EXTERNAL THREAD ALUMINIUM THREAD G 1/2 INCH 20.95 MM

SKU: 4015448876755

Pushbutton-Safety coupling DN 7.4, external thread aluminium thread G 1/2 inch 20.95 mm

Categories: Compressed air fittings, Compressed air Technology

Product Features: Type: DN 7.4, external

thread

Length: 73.3 mm Thread: G 1/2

Temperature range: - 20 to 70 °C Temperature of medium: - 20 to 70 °C

Thread mm: 20.95 mm Material: Aluminium Sealing material: NBR

AF:

Scope of delivery:

1,00 ST Pushbutton-Safety coupling DN 7.4, external thread aluminium thread G 1/2 inch 20.95 mm |

PRODUCT DESCRIPTION

High-quality, robust and durable, operable with one-hand, quick-lock coupling in safe design with high flow rates

- Decoupling takes place by pressing the pushbutton twice
- The first press vents the coupling, but the plug remains secured in the coupling
- With the second press, the plug is safely released
- This consequently prevents notorious 'whiplash accidents' and virtually eliminates risk of injuring the operator
- Conforms to ISO standard DIN EN ISO 4414 Further technical information:
- Flow volume (air): 1800 (at 6 bar, mounted plug and p = 1 bar)l/min





- Flow: 1600l/min

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools All rights reserved