Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



PROMAT TWIST DRILL DIN 338 TYPE N NOMINAL DIAMETER 20 MM HSS PROFILE GROUND OFFSET SHANK OFFSET SHANK

SKU: 4015448762485

Twist drill DIN 338 type N nominal diameter 20 mm HSS profile ground offset shank offset shank

---

Categories: Drill Bits, Twist drills and accessories

Product Features: Coating: Uncoated
Nominal Ø: 20 mm
Overall length: 205 mm
Shank Ø: 13 mm
Length of spiral: 140 mm
Shank design: Offset shank
Point angle: 118 °
Type: N
Standard: DIN 338
Cutting material: HSS
Mar

Scope of delivery:
1,00 ST Twist drill DIN 338 type N nominal diameter 20 mm HSS profile ground offset shank offset shank |

PRODUCT DESCRIPTION

HSS
- DIN 338
- Type N
- Point angle 118°
- Right-hand cutting
- Crosswise grinding according to DIN 1412 C
- With offset shank
- The fully ground twist drill has a higher concentricity
- Uses : For steel, alloyed and unalloyed cast steel (up to 900 N/mm² strength grey cast, malleable iron,

Copyright © 2023 Actik Tools All rights reserved

ductile iron and die-cast, sintered iron, nickel silver, graphite, short-chipping aluminium alloys, brass and bronze
- Ideal for drilling larger bore diameters for all conventional drills with a chuck up to 13.0 mm Further technical information:
- Feed in steel up to 800 N: 0,14mm/rev
- Quality: Profile-ground
- Length of shank: 35mm

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.

Copyright © 2023 Actik Tools

All rights reserved