



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## ROBERT BOSCH POWER TOOLS GMBH ANGLE GRINDER WITH X-LOCK GWX 14-125

SKU: 4059952579108

Angle Grinder with X-LOCK GWX 14-125



**Categories:** [Angle grinder & metalworking](#),  
[BOSCH professional](#)

**Product Features:** Tool dimensions (height):

102 mm

Switch: Lockable Switch

Packaging dimensions (width): 160 mm

Packaging dimensions (length): 363 mm

Packaging dimensions (height): 134 mm

Packaging dimensions (width x length x  
height): 160 x 363 x 134 mm

Voltage, electrical: 230 V

Rated input power: 1.400 W

No-load speed, up to: 11.000 rpm

No-load speed: 11,000 rpm

Power output: 820 W

Main handle: Barrel

Disc diameter: 125 mm

Rubber backing pad, diameter: 125 mm

Wire cup brush, diameter: 75 mm

Tool dimensions (width): 298 mm

Tool dimensions (length): 102 mm

Weight: 2,3 kg

Vibration emission value ah [Surface grinding  
(roughing)]: 8,5 m/s<sup>2</sup>

Uncertainty K [Surface grinding (roughing)]:  
1,5 m/s<sup>2</sup>

Vibration emission value ah [Sanding with  
sanding sheet]: 3,0 m/s<sup>2</sup>

Uncertainty K [Sanding with sanding sheet]:  
1,5 m/s<sup>2</sup>

Product category subdivision: Angle Grinder  
with X-LOCK

Positioning: Tough grinding performance  
with versatility for regular use in the 1,400 W



category - with X-LOCK

User benefit incl. Reason to believe: Constant electronics maintains consistent speed during operation even under load

User benefit incl. Reason to believe: Changing accessories is fast and convenient thanks to keyless X-LOCK click system

User benefit incl. Reason to believe: Optimised motor cooling makes tool capable of managing high overloads

Positioning (BE): Tough grinding performance with versatility for regular use in the 1,400 W category - with X-LOCK

User benefit incl. Reason to believe (BE): Constant electronics maintains consistent speed during operation even under load

User benefit incl. Reason to believe (BE): Changing accessories is fast and convenient thanks to keyless X-LOCK click system

User benefit incl. Reason to believe (BE): Optimised motor cooling makes tool capable of managing high overloads

Areas of application: Cutting concrete

Areas of application: Cutting ferrous metals

Areas of application: Cutting wood

Areas of application: Cutting synthetic material

Areas of application: Cutting non-ferrous metal

Areas of application: Cutting stone

Areas of application: Sanding ferrous metals

Areas of application: Sanding non-ferrous metal

Areas of application: Brushing coating material

Areas of application: Brushing ferrous metals

Areas of application: Brushing non-ferrous metal

Areas of application: Dry drilling in stone

Title: Angle Grinder with X-LOCK GWX 14-125 Professional

Novelty: no

Novelty until: 30.04.2021

Scope of supply: 1 x diamond cutting blade X-LOCK, Standard for Universal, 125 x 22.23 x 1.6 x 10 mm (2 608 615 166)

Scope of supply: Protective guard (1 605 510 365)



Scope of supply: Auxiliary handle (spare part number 2 602 025 067)

Scope of supply: Cardboard box

SOL Date: 01.09.2020

Scope of delivery:

1 ST Angle Grinder with X-LOCK GWX 14-125

|

## PRODUCT DESCRIPTION

Angle Grinder with X-LOCK GWX 14-125, The GWX 14-125 Professional corded angle grinder with X-LOCK offers tough grinding performance with versatility for regular use in the 1,400 W category. Its constant electronics maintains a consistent speed during operation even under load. An optimised motor cooling makes this small angle grinder capable of managing high overloads. Furthermore, it comes with a keyless X-LOCK click system that enables fast and convenient accessory changes. This tool is intended for cutting and grinding metal, tiles, and bricks. It is compatible with dust attachments GDE 125 EA-T Professional and GDE 115 / 125 FC-T Professional. The GWX 14-125 Professional also features direct motor cooling, protection guard, restart protection, and soft start. 1 x diamond cutting blade X-LOCK, Standard for Universal, 125 x 22.23 x 1.6 x 10 mm (2 608 615 166); Protective guard (1 605 510 365); Auxiliary handle (spare part number 2 602 025 067); Cardboard box

Article ID: 06017B7001

### PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.