



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH BIM PLUNGE CUT SAW BLADE AIZ 32 APB WOOD AND METAL. FOR OSCILLATING MULTITOOLS

SKU: 3165140665957

BIM plunge cut saw blade AIZ 32 APB Wood and Metal. For oscillating multitools

Categories: [Accessories for BOSCH professional](#), [Accessories for multifunctional tools](#)

Product Features: Material: BIM

Width [mm]: 32

Immersion depth [mm]: 50

Benefit HL (short): Precise Plunge Cuts in Wood and Metal

Performance Claim Text: Precise Plunge Cuts (Version) Key RTB: Precise cuts due to rounded cutting edge called Curved-Tec Specific RTB1: Sturdy Starlock mounting system increases control for highly accurate cutting

Specific RTB2: BIM combination of HCS blade and HSS teeth resists wear and heat for longer life

Specific RTB3: Starlock Snap-In mounting system for fast blade removal and exchange within 3 seconds without having to touch the blade

Material: Wood with nails

Material: Metal sandwich

Material: Plastic coated boards

Material: Plastics

SOL Date: 01.01.2016

Novelty: no

Scope of delivery:

25 ST BIM plunge cut saw blade AIZ 32 APB Wood and Metal. For oscillating multitools |



PRODUCT DESCRIPTION

The Starlock AIZ 32 APB blade guarantees exact flush and deep plunge cuts in wood, metal and plastics. It cuts precisely right from the start thanks to a rounded cutting edge called Curved-Tec. The blade's Starlock sturdy mounting system increases control for highly accurate cutting that transmits power directly and reduces wobbling. This versatile blade also cuts through very hard combined wooden and metal materials including non-hardened nails and screws, non-ferrous pipes and profiles with smaller dimensions. High wear and heat resistant teeth made from HSS-Steel (High Speed Steel) offer a long lifetime in non-ferrous (soft) metal and abrasive materials. The Starlock Snap-In mounting system allows fast blade removal and exchange within 3 seconds without having to touch the blade. The mounting system produces the highest power transfer thanks to a 3-dimensional tight-fitting connection between machine and accessory.

Article ID: 2608661902

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.