



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH BIM SERRATED SEGMENT BLADE ACZ 100 SWB. FOR OSCILLATING MULTITOOLS

SKU: 3165140546737

BIM serrated segment blade ACZ 100 SWB.
For oscillating multitools

Categories: [Accessories for BOSCH professional](#), [Accessories for multifunctional tools](#), [Saws](#)

Product Features: Material: BIM
Cutting width [mm]: 100
Benefit HL (short): Fast Cuts in Various Soft Materials
Performance Claim Text: Fast Cuts in Various Soft Materials
(Version) Key RTB: Serrated blade enables faster results than smooth cutting edges
Specific RTB1: Wide 100 mm diameter provides rapid work progress
Specific RTB2: BIM combination of HCS body and HSS teeth resists wear and heat for long life
Specific RTB3: Pointed segment saw blade ends enable cutting right into corners
Material: Roof felt
Material: Polystyrene PS
Material: Pipe insulation
Material: Carpet
SOL Date: 01.01.2016
Novelty: no

Scope of delivery:
1 ST BIM serrated segment blade ACZ 100 SWB. For oscillating multitools |



PRODUCT DESCRIPTION

The Starlock ACZ 100 SWB blade provides fast cuts in various rigid soft materials. It has a serrated blade enabling the edge points to grab and dig into the material for faster results than with standard smooth cutting edges. Its wide 100 mm diameter tackles a larger surface area for dynamic material removal, providing rapid work progress. It can make fast flush cuts in protruding insulation materials and cuts insulation panels and cardboard to size, along with soft materials such as linoleum, carpet and putty materials. When cutting non-hardened metals and abrasive materials, the BIM (bi-metal) combination of an HCS (high carbon steel) blade and HSS (high-speed steel) teeth resists wear and heat, ensuring a long life for the blade. The pointed segment saw blade ends enable cutting right into corners while the round blade body design enables straight cuts. The Starlock Snap-In mounting system allows fast blade removal and exchange within 3 seconds without having to touch the blade. The mounting system produces the highest power transfer due to a 3-dimensional tight-fitting connection between machine and accessory.

Article ID: 2608661693

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.