



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH C410 SANDING ROLL. FOR HAND SANDING

SKU: 3165140180870

C410 sanding roll. For hand sanding

Categories: [Accessories for BOSCH professional](#), [Grinding and polishing](#)

Product Features: Roll width mm: 115
Roll length m: 5
Grit: 240
Benefit HL (short): Good Removal Rate
Performance Claim Text: Great Removal Rate
(Version) Key RTB: Semi-friable aluminium oxide abrasive grit ensures an even and consistent material removal
Specific RTB1: An electrostatically open-coated surface enables dust extraction, preventing clogging for efficient sanding
Specific RTB2: High-quality semi-friable aluminium oxide for consistent surface quality
Specific RTB3: Fully synthetic resin binding C-backing paper for high flexibility and optimal sanding behaviour
Material: Softwood
Material: Hardwood
Material: Solid wood furniture board
Material: Parquet
Material: Multiplex board
Material: Particleboard
Material: Plastic coated boards
Product text, Accessories grey: 5 m
SOL Date: 01.07.2015
Novelty: no

Scope of delivery:
4 ST C410 sanding roll. For hand sanding |



PRODUCT DESCRIPTION

The C410 Standard for Wood and Paint has a great material removal rate when hand-sanding wood and paint. This all-round hand-sanding product ensures an even and consistent material removal due to its tough semi-friable aluminium oxide abrasive grit coating. Furthermore, its electrostatically open coated surface enables good dust extraction, preventing clogging for efficient sanding and clean surface results. It is intended for the general hand sanding of wood, wood-based materials and veneer as well as solid surfaces and is suitable for intermediate sanding for varnishes on surfaces and roundings. It is also ideal for keying and sanding down paint, varnish and fillers as well as keying and fine sanding out feathered edges, primer and filler. This sheet is coated with tough semi-friable aluminium oxide for consistent surface quality. It is electrostatically open coated, which enables consistent material removal. Furthermore, the grit is bonded with fully synthetic resin on C-backing paper for high flexibility and optimal sanding behaviour.

Article ID: 2608606822

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.