



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH CARBIDE-RIFF SEGMENT SAW BLADE MATI 68 RST5. FOR OSCILLATING MULTITOOLS

SKU: 3165140833219

Carbide-RIFF segment saw blade MATI 68 RST5. For oscillating multitools

Categories: [Accessories for BOSCH professional](#), [Accessories for multifunctional tools](#)

Product Features: Material: Carbide RIFF
Cutting width [mm]: 1,5
Width [mm]: 68
Length [mm]: 10
Grit: 50
Benefit HL (short): Extra-Thin and Fast Routing in Grout and Abrasive
Performance Claim Text: Extra-Thin and Fast Routing
(Version) Key RTB: Extremely thin blade with a 1.5 mm cutting width creates precise fine cuts and routes
Specific RTB1: Blade design with pointed edges for reaching into tight spaces and corners
Specific RTB2: Extra-fine carbide grit 50 edge creates clean thin cuts
Specific RTB3: Carbide grit for very long lifetime
Material: Mortar
Material: Fibre cement boards
Material: Fibre plastics GFK, CFK
Material: Aerated concrete
SOL Date: 01.01.2016
Novelty: no

Scope of delivery:
1 ST Carbide-RIFF segment saw blade MATI



PRODUCT DESCRIPTION

The Starlock MATI 68 RST5 blade ensures extra-thin and fast results when routing grout and abrasive. Its thin blade with a 1.5 mm cutting width routes very thin joints and creates fine cuts. The blade's design features pointed edges for reaching into tight spaces and corners. A high-quality fine carbide grit 50 covers the extra-slender cutting edge for making distinctively clean thin cuts. This accessory offers perfect results when routing extra-thin grout joints between tiles, even in the most hard-to-reach spaces. The blade is suitable for routing grooves in porous concrete and soft brick. It also cuts precise recesses in abrasive materials such as cement-bonded fibre boards and glass fibre-reinforced composites. Tough carbide grit 50 ensures strong wear resistance and an extra-long life. The Starlock Max system offers maximum depth, speed and versatility in even the most demanding heavy-duty applications. The Starlock Snap-In mounting system allows fast blade removal and exchange within 3 seconds without having to touch the blade. The mounting system produces the highest power transfer due to a 3-dimensional tight-fitting connection between machine and accessory.

Article ID: 2608662578

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.