



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.

## ROBERT BOSCH POWER TOOLS GMBH COMBI LASER GCL 2-15

**SKU:** 3165140837224

Combi Laser GCL 2-15



**Categories:** [BOSCH professional](#), [Measuring equipment](#)

**Product Features:** Laser diode: 630 - 650 nm, < 1mW

Operating temperature, from: -10 °C

Operating temperature, up to: 50 °C

Operating temperature: -10 - 50 °C

Storage temperature, from: -20 °C

Storage temperature, up to: 70 °C

Storage temperature: -20 - 70 °C

Laser class: 2

Working range, sign: up to

Working range, value: 15 m

Working range: up to 15 m

Accuracy:  $\pm 0.3$  mm/m\* (\*plus use-dependent deviation)

Working range of laser points, max.: 10 m (top)

Working range of laser points, max.: 10 m (bottom)

Self-levelling range:  $\pm 4^\circ$

Levelling time: 4 s

Dust and splash protection: IP 54

Power supply: 3 x 1.5 V LR6 (AA)

Operating time (max.): 6 h in cross line and point mode

Operating time (max.): 8 h in cross line mode

Operating time (max.): 12 h in line and point mode

Operating time (max.): 16 h in line mode

Operating time (max.): 22 h in point mode

Tripod thread: 1/4", 5/8"

Weight, approx.: 0,49 kg

Colour of laser line: red

Projection: 2 lines / 2 points



Plumb point accuracy:  $\pm 0.7$  mm/m\* (\*plus use-dependent deviation)  
Product category subdivision: Combi Laser  
Positioning: Compact and versatile for short-distance levelling applications  
User benefit incl. Reason to believe: Both horizontal and vertical lines are perfect for short-distance levelling applications  
User benefit incl. Reason to believe: Enjoy precise transfer applications thanks to two centred plumb points  
User benefit incl. Reason to believe: Rotating mount RM 1 Professional allows laser lines to be easily positioned around the plumb points  
Title: Combi Laser GCL 2-15 Professional  
Novelty: no  
Scope of supply: Carrying case  
Scope of supply: Rotating mount RM 1 Professional (0 601 092 600)  
Scope of supply: Ceiling clamp  
Scope of supply: Laser target plate  
Scope of supply: 3 x 1.5 V LR6 battery (AA)  
SOL Date: 01.05.2015

Scope of delivery:  
1 ST Combi Laser GCL 2-15 |

## PRODUCT DESCRIPTION

Combi Laser GCL 2-15, The combi laser GCL 2-15 Professional convinces through its compact design and is especially suitable for short-distance levelling applications. By projecting both horizontal and vertical laser lines and two centred plumb points, this combi laser supports completing levelling tasks quickly. Its plumb points make precise transfer applications easy and convenient. Aligning the laser lines around the plumb points is simple thanks to its rotating mount RM 1 Professional. The GCL 2-15 Professional is suitable for various applications such as mounting shelves and windows, installing drainage pipes, and laying floors. It also offers point transfers for light mountings. The GCL 2-15 Professional provides a line laser working range of up to 15 m and self-levels in less than 4 seconds. This combi laser is ideal for use with the RM 1 Professional, which can be swiftly attached via a simple slide mechanism. It is robust thanks to IP54 dust and splash water protection. When switching off the tool, the pendulums lock-mechanism allows for safe transportation. Carrying case; Rotating mount RM 1 Professional (0 601 092 600); Ceiling clamp; Laser target plate; 3 x 1.5 V LR6 battery (AA)

Article ID: 0601066E02

### PRODUCT DATASHEET LEGAL NOTE



Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.