



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH COMBI LASER GCL 2-50 CG

SKU: 3165140865654

Combi Laser GCL 2-50 CG

Categories: [Battery-powered tools](#), [BOSCH professional](#), [Measuring equipment](#), [Networked products and services](#)

Product Features: Battery voltage: 12

Laser diode: 500 - 540 nm, < 10 mW

Laser diode: 630 - 650 nm, < 1mW

Operating temperature, from: -10 °C

Operating temperature, up to: 50 °C

Operating temperature: -10 - 50 °C

Storage temperature, from: -20 °C

Storage temperature, up to: 70 °C

Storage temperature: -20 - 70 °C

Laser class: 2

Working range, value: 20 m

Working range: 20 m

Working range with receiver, value: 50 m

Working range with receiver: 50 m

Accuracy: ± 0.3 mm/m* (*plus use-dependent deviation)

Working range of laser points, max.: 10 m (top)

Working range of laser points, max.: 10 m (bottom)

Self-levelling range: $\pm 4^\circ$

Dust and splash protection: IP 54 ***

(***except for the lithium-ion battery and AA1 battery adapter)

Operating time (max.): 10 h (Li-Ion) and 4 h (4 x AA) in cross-line and point operation

Operating time (max.): 13 h (Li-Ion) and 6 h (4 x AA) in cross-line operation

Operating time (max.): 15 h (Li-Ion) and 12 h (4 x AA) in line operation

Operating time (max.): 60 h (Li-Ion) and 32 h (4 x AA) in point operation



Tripod thread: 1/4"
Weight, approx.: 0,6 kg
Colour of laser line: green
Color of plumb points: red
Projection: 2 lines / 2 points
Plumb point accuracy: ± 0.7 mm/m* (*plus use-dependent deviation)
Compatible laser receivers: LR 7
Product category subdivision: Combi Laser
Positioning: Supreme visibility connected with smart functions
User benefit incl. Reason to believe: Bright green horizontal and vertical laser lines and two centred plumb points offer optimal visibility
User benefit incl. Reason to believe: Bluetooth®-connection paired with Levelling Remote App offers remote-control adjustment of the tool via a smartphone
User benefit incl. Reason to believe: Dual Power Source allows for the use of 12 V Li-ion battery or standard alkaline batteries
Title: Combi Laser GCL 2-50 CG Professional
Novelty: no
Novelty until: 25.06.2017
Scope of supply: Ceiling clamp
Scope of supply: Laser target plate
Scope of supply: L-BOXX 136 (1 600 A01 2G0)
Scope of supply: Protective Bag
Scope of supply: Rotating mount RM 2 Professional (0 601 092 700)
Scope of supply: 1 x battery GBA 12V 2.0Ah (1 600 Z00 02X)
Scope of supply: Quick charger GAL 12V-40 Professional (1 600 A01 9R3)
SOL Date: 25.03.2017

Scope of delivery:
1 ST Combi Laser GCL 2-50 CG |

PRODUCT DESCRIPTION

Combi Laser GCL 2-50 CG, The combi laser GCL 2-50 CG Professional offers supreme visibility with a range of smart functions. Bright green horizontal and vertical laser lines and two centred plumb points offer optimal visibility, while its Bluetooth®-connection offers remote-control adjustment via a smartphone app. For increased flexibility, Dual Power Source allows 12 V Li-ion battery or standard



alkaline batteries. This combi laser is designed for horizontal and vertical alignments with a long overshoot of nearly 360° and is suitable for projects such as dry wall installation and interior finishing tasks. The GCL 2-50 CG Professional delivers high visibility of up to 20 m without a receiver and 50 m with a receiver. For precise positioning around the plumb points, the RM 3 Professional offers motorised control, and RM 2 Professional allows for manual adjustments. Ceiling clamp; Laser target plate; L-BOXX 136 (1 600 A01 2G0); Protective Bag; Rotating mount RM 2 Professional (0 601 092 700); 1 x battery GBA 12V 2.0Ah (1 600 Z00 02X); Quick charger GAL 12V-40 Professional (1 600 A01 9R3)

Article ID: 0601066H00

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.