



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH CORDLESS DRILL/DRIVER GSR 18V-60 FC

SKU: 3165140906098

Cordless Drill/Driver GSR 18V-60 FC

Categories: [Battery-powered tools](#), [BOSCH professional](#)

Product Features: Max. screw diameter: 10 mm

Tool dimensions (height): 204 mm

Packaging dimensions (width): 360 mm

Packaging dimensions (length): 443 mm

Packaging dimensions (height): 155 mm

Packaging dimensions (width x length x height): 360 x 443 x 155 mm

Max. drilling diameter in wood: 38 mm

Battery voltage: 18.0 V

Weight incl. battery: 0,9 kg

Torque (soft): 31 Nm

Torque (hard): 60 Nm

Torque (soft/hard/max.): 31/60/- Nm

Battery type: Lithium-ion

No-load speed, 1st gear, from: 0 rpm

No-load speed, 1st gear, up to: 600 rpm

No-load speed, 2nd gear, from: 0 rpm

No-load speed, 2nd gear, up to: 1.900 rpm

No-load speed (1st gear / 2nd gear): 0 - 600 / 0 - 1,900 rpm

Chuck capacity, min.: 1,5 mm

Chuck capacity, max.: 13 mm

Chuck capacity, min./max.: 1.5 / 13 mm

Weight excl. battery: 0,9 kg

Torque settings (standard): 20

Torque settings (additional): 1

Torque settings: 20+1

Max. drilling diameter in steel: 13 mm

Vibration emission value ah [Screwdriving]: 1,5 m/s²

Uncertainty K [Screwdriving]: 0,0 m/s²



Product category subdivision: Cordless Drill/Driver

Positioning: Bosch's drill driver with FlexiClick System for any job in the 18 V category

Long version part 1: The GSR 18V-60 FC Professional cordless drill driver with FlexiClick System is perfect for any job in the 18 V category. Its Bosch FlexiClick System with several adjustable adapters provides full flexibility in every work situation. Extremely simple to operate, the Bosch FlexiClick adapters can be locked in 16 different positions, at a 360° angle, without removing them from the drill driver. A unique rotary hammer adapter turns the tool into a fully fledged SDS rotary hammer for versatile applications. This tool is intended for drilling in wood with a maximum diameter of 38 mm and in steel and masonry up to 13 mm, as well as for screw diameters of up to 10 mm. It is compatible with all Bosch Professional 18 V batteries and chargers (Professional 18V System).

Long version part 2: The GSR 18V-60 FC Professional also features 2-gear, Autolock, brushless motor, Bluetooth Connectivity module, Electronic Motor Protection, Li-ion, full-metal chuck, and precision clutch.

User benefit incl. Reason to believe: Bosch FlexiClick System with several adjustable adapters provides full flexibility in every work situation

User benefit incl. Reason to believe: Extremely simple to operate, FlexiClick adapters can be locked in 16 positions (360° angle), without removing from drill

User benefit incl. Reason to believe: Unique rotary hammer adapter turns tool into fully fledged SDS rotary hammer for versatile applications

Positioning (BE): Bosch FlexiClick System: Flexible and versatile for any job in the 18 Volt class

User benefit incl. Reason to believe (BE): Full flexibility: With several adjustable adapters, the Bosch FlexiClick system provides the optimum solution in every work situation



User benefit incl. Reason to believe (BE): Easy to operate: The Bosch FlexiClick adapters can be locked in 16 different positions (360°) without having to remove them from the cordless screwdriver

User benefit incl. Reason to believe (BE): Versatile: The unique rotary hammer adapter turns the drill/driver into a fully fledged rotary hammer

Areas of application: Drilling in concrete

Areas of application: Drilling in ferrous metals

Areas of application: Drilling in wood

Areas of application: Drilling in synthetic material

Areas of application: Drilling in non-ferrous metal

Areas of application: Drilling in stone

Areas of application: Wet drilling in concrete

Areas of application: Wet drilling in stone

Areas of application: Dry drilling in stone

Areas of application: Screwdriving

Areas of application: Brushing coating material

Areas of application: Brushing ferrous metals

Areas of application: Brushing wood

Areas of application: Brushing non-ferrous metal

Title: Cordless Drill/Driver GSR 18V-60 FC Professional

Novelty: no

Scope of supply: L-BOXX 136 (1 600 A01 2G0)

Scope of supply: L-BOXX inlay for tool

Scope of supply: Metal chuck adapter GFA 18-M Professional (1 600 A01 3P6)

Scope of supply: Off-set angle adapter GFA 18-E Professional (1 600 A00 1SJ)

Scope of supply: Angle adapter GFA 18-W Professional (1 600 A01 3P7)

Scope of supply: Hammer adapter incl. auxiliary handle GFA 18-H Professional (1 600 A00 3NF)

SOL Date: 01.01.2018

Scope of delivery:

1 ST Cordless Drill/Driver GSR 18V-60 FC |



PRODUCT DESCRIPTION

Cordless Drill/Driver GSR 18V-60 FC, The GSR 18V-60 FC Professional cordless drill driver with FlexiClick System is perfect for any job in the 18 V category. Its Bosch FlexiClick System with several adjustable adapters provides full flexibility in every work situation. Extremely simple to operate, the Bosch FlexiClick adapters can be locked in 16 different positions, at a 360° angle, without removing them from the drill driver. A unique rotary hammer adapter turns the tool into a fully fledged SDS rotary hammer for versatile applications. This tool is intended for drilling in wood with a maximum diameter of 38 mm and in steel and masonry up to 13 mm, as well as for screw diameters of up to 10 mm. It is compatible with all Bosch Professional 18 V batteries and chargers (Professional 18V System). The GSR 18V-60 FC Professional also features 2-gear, Autolock, brushless motor, Bluetooth Connectivity module, Electronic Motor Protection, Li-ion, full-metal chuck, and precision clutch. L-BOXX 136 (1 600 A01 2G0); L-BOXX inlay for tool; Metal chuck adapter GFA 18-M Professional (1 600 A01 3P6); Off-set angle adapter GFA 18-E Professional (1 600 A00 1SJ); Angle adapter GFA 18-W Professional (1 600 A01 3P7); Hammer adapter incl. auxiliary handle GFA 18-H Professional (1 600 A00 3NF)

Article ID: 06019G7103

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.