



Our retail price is a recommendation only. Prices in offer may differ. All prices indicated 0,00 € will follow in the offer.



ROBERT BOSCH POWER TOOLS GMBH CORDLESS IMPACT WRENCH GDS 18V-1050 H

SKU: 4059952564661

Cordless Impact Wrench GDS 18V-1050 H

Categories: [Battery-powered tools](#), [BOSCH professional](#), [Rotary impact wrench](#)

Product Features: No-load speed, up to:
1.750 rpm

No-load speed, 1st level, up to: 800 rpm

Tool dimensions (width): 86 mm

Tool dimensions (length): 222 mm

Tool dimensions (height): 240 mm

Packaging dimensions (width): 360 mm

Packaging dimensions (length): 443 mm

Packaging dimensions (height): 155 mm

Packaging dimensions (width x length x height): 360 x 443 x 155 mm

No-load speed, from: 0 rpm

No-load speed: 0 rpm

Battery voltage: 18.0 V

Tool holder: 3/4" Square

Breakaway torque, max.: 1700 Nm

Torque adjustment range, min. 1st level: 0 Nm

Torque adjustment range, max. 1st level: 350 Nm

Torque adjustment range, min./max., 1st level: 0/350 Nm

Torque adjustment range, min. 2nd level: 0 Nm

Torque adjustment range, max. 2nd level: 750 Nm

Torque adjustment range, min./max., 2nd level: 0/750 Nm

Torque adjustment range, min. 3rd level: 0 Nm

Torque adjustment range, max. 3rd level: 1050 Nm



Torque adjustment range, min./max., 3rd level: 0/1050 Nm
No-load speed, 1st level, from: 0 rpm
No-load speed (1st level): 0 rpm
No-load speed, 2nd level, from: 0 rpm
No-load speed, 2nd level, up to: 1.200 rpm
No-load speed (2nd level): 0-1,200 rpm
No-load speed (3rd level): 0-1,750 rpm
Torque settings: 3
Weight excl. battery: 2,9 kg
Torque, max.: 1050 Nm
Impact rate, from: 0 bpm
Impact rate, up to: 2.600 bpm
Impact rate: 0-2,600 bpm
Impact rate (1st level): 0-1,600 bpm
Impact rate (2nd level): 0-2,400 bpm
Impact rate (3rd level): 0-2,600 bpm
Screw diameter: M 14 - M 24
Vibration emission value ah [Tightening screws and nuts of maximum permitted size]: 13,5 m/s²
Uncertainty K [Tightening screws and nuts of maximum permitted size]: 1,5 m/s²
Product category subdivision: Cordless Impact Wrench
Positioning: Full power at its best: 3/4" high torque impact wrench with BITURBO Brushless technology
User benefit incl. Reason to believe: Impressive power with cordless freedom thanks to ProCORE18V batteries and brushless motor
User benefit incl. Reason to believe: High performance motor with a tightening torque of 1,050 Nm and a breakaway torque of up to 1,700 Nm
User benefit incl. Reason to believe: Ideal versatility and controlled power due to 3-speed/torque settings
Positioning (BE): Full power at its best: 3/4" high torque impact wrench with BITURBO Brushless technology
User benefit incl. Reason to believe (BE): Impressive power with cordless freedom thanks to ProCORE 18V batteries and brushless motor
User benefit incl. Reason to believe (BE): High performance motor with a tightening torque



of 1,050 Nm and a breakaway torque of up to 1,700 Nm

User benefit incl. Reason to believe (BE): Ideal versatility and controlled power due to 3-speed/torque settings

Areas of application: Screwdriving

Title: Cordless Impact Wrench GDS 18V-1050 H Professional

Novelty: no

Novelty until: 01.04.2021

Scope of supply: L-BOXX 136 (1 600 A01 2G0)

Scope of supply: 1/1 L-BOXX inlay for tool and charger (1 600 A02 58Y)

Scope of supply: Ladder clip (1600 A02 3G7)

SOL Date: 01.01.2021

Scope of delivery:

1 ST Cordless Impact Wrench GDS 18V-1050 H |

PRODUCT DESCRIPTION

Cordless Impact Wrench GDS 18V-1050 H, The GDS 18V-1050 H Professional is the outstanding 3/4" impact wrench with brushless motor for the most diverse fields of application. Its BITURBO Brushless technology combines corded power with cordless freedom fully maximised for ProCORE18V batteries. Whenever heavy-duty performance is needed, the new impact mechanism provides a tightening Torque of 1,050 Nm and breakaway torque of 1,700 Nm for particularly challenging working environments. The high versatility in power controlling is ensured by the 3-speed/torque settings that allow adjustments to the respective work requirements. The main areas of GDS 18V-1050 H Professional are metal applications (M10-M24) like structural steel construction, metal assembly, pipe fitting, truck maintenance, and wood construction. It is compatible with all Bosch Professional 18 V batteries and chargers (Professional 18V System), for maximum power use ProCORE18V 5.5 Ah. The GDS 18V-1050 H Professional comes with additional figures like ECP, EMP, a tool status indicator, LED light, a 3/4" tool holder with friction ring plus through hole, and a ladder clip. L-BOXX 136 (1 600 A01 2G0); 1/1 L-BOXX inlay for tool and charger (1 600 A02 58Y); Ladder clip (1600 A02 3G7)

Article ID: 06019J8501

PRODUCT DATASHEET LEGAL NOTE

Please note that the information on this datasheet is provided without warranty and is intended only as non-binding information about the product. Any liability for damages or losses that may arise from the use of this information is excluded. We therefore recommend that you verify the information on this datasheet with other sources before making any decisions based on this information. Additional information about the product can be found on our website.